ZS1052-0610 www.beckhoff.com/ZS1052-0610



## ZS1052-0610 | Plug CANopen/DeviceNet, IP67

M12, plug, straight, male, 5-pin, A-coded




| Electrical data                       |   |
|---------------------------------------|---|
| Rated voltage                         | 60 V (according to IEC 61076-2-101)           |
| Rated current                         | 7,5 A at 40 °C (according to IEC 61076-2-101) |
| Insulation resistance                 | ≥ 100 M $\Omega$ (according to IEC 60512)     |
| Mechanical data                       |   |
| Installation size                     | M12   |
| Connector type                        | plug  |
| Configuration                         | straight                                      |
| Contact type                          | male  |
| Number of positions (face)            | 5-pin   |
| Coding                                | A-coded                                       |
| Recommended torque, nut               | 0.6 Nm  |
| Recommended torque, screw termination | 0.3 Nm  |
| Mating cycles                         | ≥ 100 (according to IEC 60512-9a)             |
| Body material                         | PA6 GF, UL 94 HB                              |
| Coupling nut material                 | CuZn, Ni                                      |

ZS1052-0610 www.beckhoff.com/ZS1052-0610

| Seal                            | elastomers  |
|---------------------------------|---|
| O-ring                          | FPM/NBR   |
| Contact carrier material        | PA 6, UL 94 V0  |
| Contact material                | CuZn, Ni b/Au 0.2 gal.                                |
| Max. wire cross-section         | AWG16 (1.5 mm²)                                       |
| Max. cable outer diameter       | 4 - 8 mm  |
| Environmental data              |   |
| Ambient temperature (operation) | -30+85 °C, -22+185 °F                                 |
| Protection rating               | IP65/67 in screwed condition (according to IEC 60529) |
| Pollution level                 | 3/2 (according to IEC 60664-1)                        |

## **Dimensions**





| A1 | 57.0 mm   |
|----|-----------|
| A2 | Ø 20.0 mm |

## **Notes**

- Illustrations similar

| Ordering information |  |
|----------------------|--|
| ZS1052-0610          | Plug CANopen/DeviceNet, IP67, M12, straight, male, schraub, 5-pin, A-coded |
|                      |  |

| Accessories |  |
|-------------|--|
| ZB8801-0000 | torque wrench for hexagonal plugs, adjustable          |
| ZB8801-0003 | torque cable key, M12F/wrench size 18, for ZB8801-0000 |



Products marked with a crossed-out wheeled bin shall not be discarded with the normal waste stream. The device is considered as waste electrical and electronic equipment. The national regulations for the disposal of waste electrical and electronic equipment must be observed.

ZS1052-0610 www.beckhoff.com/ZS1052-0610

Beckhoff®, TwinCAT®, TwinCAT/BSD®, TC/BSD®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, Safety over EtherCAT®, TwinSAFE®, XFC®, XTS® and XPlanar® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 06/2023

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressively agreed in the terms of contract.

