ZS2000-4722

ZS2000-4722 | M12 Y splitter, IP67

M12, Y splitter, straight, male+female, 5-pin, A-coded




Electrical data	
Rated voltage	30 V (according to IEC 61076-2-101)
Rated current	4 A at 40 °C (according to IEC 61076-2-101)
Shielding	no
Insulation resistance	\geq 10 G Ω (according to IEC 60512-2)
Mechanical data	
Installation size	M12
Connector type	Y splitter
Configuration	straight
Contact type	male+female
Number of positions (face)	5-pin
Coding	A-coded
Recommended torque, nut	0.6 Nm
Mating cycles	≥ 100 (according to IEC 60512-9a)
Body color	black
Body material	TPU
Seal	FPM


ZS2000-4722 www.beckhoff.com/ZS2000-4722

Contact carrier material	TPU
Contact material	CuZn, Ni b/Au 0.2 gal.
Environmental data	
RoHS compliant	yes
Ambient temperature (operation)	-25+85 °C, -13+185 °F
Protection rating	IP65/67 in screwed condition (according to IEC 60529)
Pollution level	3/2 (according to IEC 60664-1)

Contact assembly



Dimensions



Notes

- Illustrations similar

Ordering information	
ZS2000-4722	Y splitter, 1 x M12 (plug) – 2 x M12 (socket), IP67, straight, 5-pin, A-coded, unshielded

Accessories	
ZB8801-0000	torque wrench for hexagonal plugs, adjustable



ZS2000-4722 www.beckhoff.com/ZS2000-4722

ZB8801-0002

torque cable key, M12/wrench size 13, for ZB8801-0000



Products marked with a crossed-out wheeled bin shall not be discarded with the normal waste stream. The device is considered as waste electrical and electronic equipment. The national regulations for the disposal of waste electrical and electronic equipment must be observed.

Beckhoff®, TwinCAT®, TwinCAT/BSD®, TC/BSD®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, Safety over EtherCAT®, TwinSAFE®, XFC®, XTS® and XPlanar® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 06/2023

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressively agreed in the terms of contract.

