


ZK4504-8027-xxxx | Motor connection cable 10 mm² with M40 speedtec[®] plug, drag-chain suitable



M40, plug, straight, female, Power: 4+PE, Signal: 4, Data: 2 – open end, 8-wire + shield – Pitch dimension 5.08 mm, plug, straight, female, 5-pin



Plugs

Electrical data	Head A	Head B	Head C
Rated voltage (power)	630 V AC / 850 V DC	-	-
Rated voltage (signal/24V)	150 V AC/DC	-	300 V (accordig to UL 1059)
Rated current (power)	70 A max.	-	-
Rated current (signal/24V)	7 A max.	-	16 A at 40 °C (according to IEC 60664-1, IEC 61984), 10 A at 40 °C (according to UL 1059)
Rated impulse voltage (power)	6.0 kV	-	-
Rated impulse voltage (signal/24V)	2.5 kV	-	4.0 kV
Contact resistance	< 5 mΩ (signal), < 1 mΩ (power)	-	< 5 mΩ
Insulation resistance	-	-	≥ 100 MΩ (according to IEC 60512)
Insulation group	-	-	IIIa

Mechanical data			
Accessories type	Connectors/Cables	-	Connectors/Cables
Installation size	M40	open end	Pitch dimension 5.08 mm
Connector type	plug	-	plug
Configuration	straight	-	straight
Contact type	female	-	female
Number of positions (face)	Power: 4+PE, Signal: 4, Data: 2	8-wire + shield	5-pin
Wire termination	crimp connection	-	Clamping yoke connection
Recommended torque, screw termination	-	-	0.4...0.5 Nm
Mating cycles	500	-	25
Way of locking	Speedtec®	-	-
Weight per piece	0.450 kg (0.9921 lb)	-	0.008 kg (0.0018 lb)
Body color	metal	-	black, similar to RAL 9011
Body material	zinc diecast/nickel plated	-	PBT, UL 94 V-0
Seal	FKM	-	-
Clamp ring	zinc diecast/nickel plated	-	-
Contact carrier material	PA 6.6 mod., UL 94 V-0	-	PBT, UL 94 V-0
Contact material	brass/gold plated	-	copper alloy
Max. wire cross-section	-	-	AWG26 ... AWG12 (0.13 mm ² ... 4 mm ²)

Environmental data			
Special features	Max. height for operation 2000 m	-	-
Ambient temperature (operation)	-20...+130°C, -4...+266°F	-	-50...+100°C, -58...+212°F
Protection rating	IP66/67 in screwed condition	-	-
Pollution level	3 (according to VDE 0110/EN61984 part 6.19.2.2)	-	3
Overvoltage category	3 (according to VDE 0110/EN61984 part 6.19.2.2)	-	3


Cable

Electrical data	
Operating voltage	max. 1000 V AC (UL), U ₀ /U 600/1000 V (VDE)
Insulation resistance	≥ 500 MΩ * km (DIN EN 50395)
Mutual capacitance	Signal: 45 ± 15 pF/m, Power: 90 pF/m (at 800 Hz according to EN 50289-1-5)


Wire resistance (power)	≤ 1.91 Ω/km (DIN EN 50395)
Wire resistance (signal/24V)	≤ 55.0 Ω/km (DIN EN 50395)
Wire resistance (brake)	≤ 13.3 Ω/km (DIN EN 50395)
Characteristic impedance	Signal: 110 Ω ± 10 Ω (10 MHz) acc. to EN50289-1-11
Dielectric strength wire/wire (power)	4 kV 50 Hz 5 min. (DIN VDE 0472 T.509C)
Dielectric strength wire/shield (power)	4 kV 50 Hz 5 min. (DIN VDE 0472 T.509C)
Dielectric strength wire/wire (signal/24V)	3 kV 50 Hz 1 min. (DIN VDE 0472 T.509C)
Dielectric strength wire/shield (signal/24V)	3 kV 50 Hz 1 min. (DIN VDE 0472 T.509C)
Mechanical data	
Cross-section (power)	10 mm ² (approx. AWG8)
Cross-section (signal)	AWG22 (approx. 0.34 mm ²)
Cross-section (brake)	1.50 mm ² (approx. AWG16)
Outer cable diameter	20.9 mm ± 0.5 mm (0.8228" ± 0.0197")
Min. bending radius, moved in drag-chain	10 x outer cable diameter
Min. bending radius, fixed installation	5 x outer cable diameter
Weight	760 kg/km (510.644 lb/1000 ft)
Conductor material	copper bare
Optical covering factor of shielding	≥ 85%
Use	drag-chain suitable
Max. acceleration	30 m/s ² by 5 m travel distance 15 m/s ² by 10 m travel distance 5 m/s ² by 20 m travel distance
Max. speed	4 m/s
Max. travel distance	20 m (horizontal) 5 m (vertical)
Max. number of cycles	5 million
Jacket color	orange
Material jacket	TPU (thermoplastic polyurethane)
Wire insulation material	PP (polypropylene)
Printing color	black
Torsion angle in °/m	max. ± 30 °/m
Max. tensile load, dynamic	20 N/mm ²
Max. tensile load, static	50 N/mm ²
Environmental data	
Operation temperature range, moved	-20...+80°C, -4...+176°F. In drag-chain with mechanical strain: -20...+60°C, -4...+140°F
Operation temperature range, fixed installation	-40...+80°C, -40...+176°F

Oil resistance	according to DIN EN 60811-404, HD22.10 appendix A
Flame-retardant	according to IEC 60332-1-2 UL758 cable flame test
CFC-free	yes
Halogen-free	according to DIN VDE 0472 Teil 815
Silicone-free	yes
RoHS compliant	yes
Approvals	UL758 (AWM) Style 21223 (jacket) and Style 10492 (core)

Contact assembly



Dimensions



A1	100.00 mm
A2	46.00 mm
C1	20.00 mm
C2	27.00 mm

Notes

- Depending on the cable length (L), the following length tolerances apply: $\pm 2-3\%$
- Illustrations similar
- The last three digits of the ordering information is the cable length in decimeters, e.g. ZK4xxx-xxxx-x020 = cable length 2.00 m

Ordering information

Length

ZK4504-8027-xxxx

xxxx = cable length in decimeters

xxxx = 0050

example for 5 m length

sold by the meter, admissible total cable length see documentation of Servo Drive

Beckhoff®, TwinCAT®, TwinCAT/BSD®, TC/BSD®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, Safety over EtherCAT®, TwinSAFE®, XFC®, XTS® and XPlanar® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 02/2024

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.