


# ZK4506-8018-xxxx | Motor connection cable 16 mm<sup>2</sup> with M40 cable gland, drag-chain suitable



M40, cable gland, straight – open end, 8-wire + shield – plug, straight, female, 5-pin



## Plugs


Electrical data	Head A	Head B	Head C
Rated voltage (signal/24V)	-	-	300 V (accordig to UL 1059)
Rated current (signal/24V)	-	-	21 A at 40 °C (according to IEC 60664-1, IEC 61984), 20 A at 40 °C (according to UL 1059)
Rated impulse voltage (signal/24V)	-	-	4.0 kV
Contact resistance	-	-	< 5 mΩ
Insulation resistance	-	-	≥ 100 MΩ (according to IEC 60512)
Insulation group	-	-	IIIa
Mechanical data			
Accessories type	-	-	Connector/cable
Installation size	M40	open end	-
Connector type	cable gland	-	plug



Configuration	straight	-	straight
Contact type	-	-	female
Number of positions (face)	-	8-wire + shield	5-pin
Wire termination	-	-	Clamping yoke connection
Recommended torque, screw termination	-	-	0.4...0.5 Nm
Mating cycles	-	-	25
Way of locking	screw	-	-
Weight per piece	0.135 kg (0.2976 lb)	-	0.008 kg (0.0018 lb)
Body colour	metal	-	black, similar to RAL 9011
Body material	brass/nickel plated	-	PBT, UL 94 V-0
Seal	elastomers	-	-
O-ring	elastomers	-	-
Contact carrier material	-	-	PBT, UL 94 V-0
Contact material	-	-	copper alloy
Max. wire cross section	-	-	AWG26...AWG12
<b>Environmental data</b>			
Ambient temperature (operation)	-25...+100 °C, -13...+212 °F	-	-50...+100 °C, -58...+212 °F
Protection class	IP 68 at 10 bar / 30min (according to DIN EN 60529)	-	-
Pollution level	-	-	3
Overvoltage category	-	-	3

## Cable

<b>Electrical data</b>			
Operating voltage	max. 1000 V AC (UL)		
Insulation resistance	≥ 500 MΩ * km (DIN EN 50395)		
Wire resistance (power)	≤ 1.21 Ω/km (DIN EN 50395)		
Wire resistance (brake)	≤ 13.3 Ω/km (DIN EN 50395)		
Dielectric strength wire/wire (power)	4 kV 50 Hz 5 min. (DIN VDE 0472 T.509C)		
Dielectric strength wire/shield (power)	4 kV 50 Hz 5 min. (DIN VDE 0472 T.509C)		
<b>Mechanical data</b>			
Cross section (power)	16 mm <sup>2</sup> (approx. AWG5)		
Cross section (brake)	1.50 mm <sup>2</sup> (approx. AWG16)		
Min. bending radius, moved in drag chain	10 x outer cable diameter		
Min. bending radius, fixed installation	5 x outer cable diameter		

Outer cable diameter	23.0 mm ± 0.5 mm (0.9055" ± 0.0197")
Conductor material	Copper bare
Optical covering factor of shielding	≥ 85%
Use	drag-chain suitable
Max. acceleration	5 m/s <sup>2</sup> (depending on travel distance)
Max. speed	3 m/s
Max. number of cycles	10 million
Wall thickness of wire insulation (power)	0.7 mm
Wall thickness of wire insulation (brake)	0.4 mm
Wall thickness of jacket	1.6 mm
Jacket colour	orange
Material jacket	PUR (polyurethane)
Wire insulation material	PP (polypropylene)
Printing colour	black
Torsion angle in °/m	max. ± 30 °/m
<b>Environmental data</b>	
Operation temperature range, moved	-30...+80 °C, -22...+176 °F, in drag-chain applications: -20...+60 °C, -4...+140 °F
Operation temperature range, fixed installation	-50...+80 °C, -58...+176 °F
Oil resistance	according to DIN EN 60811-2-1, HD22.10 appendix A
Flame-retardant	according to IEC 60332-1-2 UL758 cable flame test
Halogen-free	DIN VDE 0472 part 815
Silicone-free	yes
RoHS compliant	yes
Approvals	UL758 (AWM) Style 20234 (jacket) and Style 10492 (core)

**Contact assembly****Dimensions**



A1	50.00 mm
A2	45.00 mm
C1	20.00 mm
C2	27.00 mm

## Notes

- Depending on the cable length (L), the following length tolerances apply:  $\pm 2-3 \%$
- Illustrations similar
- The last three digits of the ordering information is the cable length in decimetres, e.g. ZK4xxx-xxxx-x020 = cable length 2.00 m

Ordering information	Length
ZK4506-8018-xxxx	xxxx = cable length in decimetres
xxxx = 0050	example for 5 m length
	sold by the metre, admissible total cable length see documentation of Servo Drive

Beckhoff®, TwinCAT®, TwinCAT/BSD®, TC/BSD®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, Safety over EtherCAT®, TwinSAFE®, XFC®, XTS® and XPlanar® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 09/2021

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.