



ZS4000-2119 | EMC power coupling


itec[®] (Series 915), socket, straight, male, Power: 3+PE, Signal: 5



Electrical data	
Rated voltage (power)	630 V AC/DC
Rated voltage (signal/24V)	63 V AC/DC
Rated current (power)	14 A
Rated current (signal/24V)	3.6 A
Rated impulse voltage (power)	6.0 kV
Rated impulse voltage (signal/24V)	1.5 kV
Contact resistance	< 5 mΩ
Mechanical data	
Accessories type	Connectors/Cables
Installation size	itec [®] (Series 915)
Connector type	socket
Configuration	straight
Contact type	male
Number of positions (face)	Power: 3+PE, Signal: 5
Wire termination	crimp connection
Mating cycles	500

Way of locking	bayonet
Weight per piece	0.035 kg (0.0772 lb)
Body material	zinc diecast/plastic
Seal	FKM
Clamp ring	brass/nickel plated
Contact carrier material	PBT, PA, UL 94 V-0
Contact material	brass/gold plated
Max. wire cross-section	AWG16 (1.5 mm ²)
Max. cable outer diameter	10.5 - 12.0 mm
Environmental data	
Special features	Max. height for operation 2000 m
Shock resistance	30 g (conforms to EN 60060-2-27), 11 ms; 18 shocks per direction, 3 axes
Vibration resistance	10 g (conforms to EN 60068-2-27), 50 Hz...2000 Hz; 1 Octave/min.; 10 cycles per axis
Ambient temperature (operation)	-20...+130 °C, -4...+266 °F
Protection rating	IP66/67 in screwed condition
Pollution level	3 (according to VDE 0110/EN61984 part 6.19.2.2)
Overvoltage category	3 (according to VDE 0110/EN61984 part 6.19.2.2)

Dimensions



A1	44.00 mm
A2	19.00 mm

Notes

- Illustrations similar

Ordering information

ZS4000-2119	EMC power coupling (male), itec [®] , 9-pol, for motor extension cable ZK4701-0421-xxxx/ZK4704-0461-xxxx (counter part for motor cable at: AM81xx with OCT feedback)
-------------	---

Beckhoff[®], TwinCAT[®], TwinCAT/BSD[®], TC/BSD[®], EtherCAT[®], EtherCAT G[®], EtherCAT G10[®], EtherCAT P[®], Safety over EtherCAT[®], TwinSAFE[®], XFC[®], XTS[®] and XPlanar[®] are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 01/2023

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.